

Angle is a range of varying products united by a common feature, tilting reflectors. This allows the downlight reflector to be adjusted, and accent lighting on vertical planes, as required. Especially suitable for commercial establishments.

Features:

Injected aluminium housing and exterior trim. High-purity aluminium faceted reflector. Steel spring clips. Tilting system and adjustment for the optic group at any point on semi-sphere.



LED personalisation

Option to incorporate new light sources designed to offer excellent colour reproduction to create products for very specific segments. On request.



Disperfum, Spain

Power

LED 25W, 37W

Beam

LED 20°, 40°

Colour temperature

3000K warm white - CRI \geq 80

4000K neutral white - CRI \geq 80

Nominal lumen output

LED 25W - 3500 lm, 37W - 5100 lm

Control gear

Electronic (EL)

Electronic Dimmer (ELD)

Electronic Dimmer Dali (ELDD)

IP

IP20 /44

Finishes

White (33)

Grey (21)

Supply voltage

220... 240V, 50/60Hz

Installation

Recessed ceiling

Features



Protective Glass

Finishes




To complete the product reference, add finish

Versions:

Special LED versions on request
2700 K and 5000 K versions on request



LED and control gear included




■ ■ 25W 20° drill-hole Ø143 control-gear EL 3500 lm 3000K 0161/L8320 4000K 0161/L8420	■ ■ 25W 20° drill-hole Ø143 control-gear ELD 3500 lm 3000K 0161/L8320D 4000K 0161/L8420D	■ ■ 25W 20° drill-hole Ø143 control-gear ELDD 3500 lm 3000K 0161/L8320DD 4000K 0161/L8420DD
--	---	--

■ ■ 25W 40° drill-hole Ø143 control-gear EL 3500 lm 3000K 0161/L8340 4000K 0161/L8440	■ ■ 25W 40° drill-hole Ø143 control-gear ELD 3500 lm 3000K 0161/L8340D 4000K 0161/L8440D	■ ■ 25W 40° drill-hole Ø143 control-gear ELDD 3500 lm 3000K 0161/L8340DD 4000K 0161/L8440DD
--	---	--



LED and control gear included



■ ■ 37W 20° drill-hole Ø175 control-gear EL 5100lm 3000K 0163/L8320 4000K 0163/L8420	■ ■ 37W 20° drill-hole Ø175 control-gear ELD 5100lm 3000K 0163/L8320D 4000K 0163/L8420D	■ ■ 37W 20° drill-hole Ø175 control-gear ELDD 5100lm 3000K 0163/L8320DD 4000K 0163/L8420DD
---	--	---

■ ■ 37W 40° drill-hole Ø175 control-gear EL 5100lm 3000K 0163/L8340 4000K 0163/L8440	■ ■ 37W 40° drill-hole Ø175 control-gear ELD 5100lm 3000K 0163/L8340D 4000K 0163/L8440D	■ ■ 37W 40° drill-hole Ø175 control-gear ELDD 5100lm 3000K 0163/L8340DD 4000K 0163/L8440DD
---	--	---

Reference options

0163/L0120/21



016 ■ /L ■ ■ ■ ■ / ■ ■ ■ ■

1- 25W
3- 37W

- 00- Fashion
- 01- Vegetables
- 82- 2700K
- 83- 3000K
- 84- 4000K
- 85- 5000K
- 06- Meat
- 07- Sausages
- 08- Fish
- 09- Bakery

20- 20°
40- 40°

21- Grey
33- White

Reference options for control gear

016 ■ /L ■ ■ ■ ■ D/ ■ ■
D= Dim 1-10V

016 ■ /L ■ ■ ■ ■ DD/ ■ ■
DD= DALI