

Linear, elegant luminaire with personality. Long-lasting, with excellent visual comfort, chromatic quality, and high efficiency. It includes high-flow, high-efficiency LEDs to fit on the surface or orientable to the wall perfect to wash walls in interior spaces.

**Features:**

Extruded, painted aluminium profile. Side and front covers of painted steel. Adjustable 90°.



**Power**

LED 9W - 13,5W - 18W

**Beam**

25°, 26°x33°

**Colour Temperature**

3000K warm white - CRI ≥ 80

4000K neutral white - CRI ≥ 80

**Nominal lumen output**

9W - 710lm, 13,5W - 1060lm, 18W - 1420lm

**Control gear**

Electronic (EL)

**IP**

IP20

**Finishes**

White [33]

Black [04]

**Supply voltage**

24VDC

Features



Finishes




To complete the product reference, add finish

LED



LED included



9W  
25°  
710 lm  
3000K **140AP/L0683M**  
4000K **140AP/L0684M**



13,5W  
25°  
1060 lm  
3000K **140AP/L0983M**  
4000K **140AP/L0984M**



18W  
25°  
1420 lm  
3000K **140AP/L1283M**  
4000K **140AP/L1284M**



9W  
26°x33°  
710 lm  
3000K **140AP/L0683EL**  
4000K **140AP/L0684EL**



13,5W  
26°x33°  
1060 lm  
3000K **140AP/L0983EL**  
4000K **140AP/L0984EL**



18W  
26°x33°  
1420 lm  
3000K **140AP/L1283EL**  
4000K **140AP/L1284EL**

Auxiliary equipment IP20

Power supply 120-240Vac/24V 100W

**71/LD10024**

Light dimming controller 12-24V. On/off, push, DALI, 0-10V, 1-10V

**73/DLP**

Light dimming controller 12-24V. On/off, push, DALI, 0-10V, 1-10V (slave)

**73/DLS**