

Adjustable recessed LED downlight aimed at a professional audience looking for a degree of differentiation. Suitable for commercial, domestic spaces, or corporate headquarters seeking differential attributes such as energy saving, small size lights, durability and a perfect light beam.

#### Features:


Downlight built with a die-cast aluminium body, injected aluminium diffuser. Cardan rotation system adjustable 30 degrees in two directions  
High-quality aluminium reflectors. Latest generation LEDs and incorporated electronic system

1-10V and DALI dimmable versions available.



#### LED personalisation

Option to incorporate new light sources designed to offer excellent colour reproduction to create products for very specific segments. On request.



7W - IP20 / 65



7W - IP20 / 44



7W - IP20 / 44



13W, 18W, 25W, 32W - IP20 / 44



#### Power

LED 7W, 13W, 18W, 25W, 32W

#### Beam

LED 7W 20°, 40°, 50°

LED 13W 15°, 24°, 36°

LED 18W 15°, 24°, 36°

LED 25W 15°, 24°, 36°

LED 32W 15°, 24°, 36°

#### Colour temperature

3000K warm white - CRI ≥ 80

4000K neutral white - CRI ≥ 80

#### Nominal lumen output

7W - 650 lm, 700 lm, 13W - 1600 lm,

18W - 2300 lm, 25W - 3100 lm, 32W - 4200 lm

#### Control gear

Electronic (EL)

Electronic Dimmer (ELD)

Electronic Dimmer Dali (ELDD)

#### IP

IP 20 / 44 - LED 7W

IP 20 / 65 - LED 7W

IP 20 / 44 - LED 13W, 18W, 25W, 32W

#### Finishes

White (33)

Black (04)

#### Supply voltage

220... 230V, 50/60Hz

#### Installation

Recessed ceiling

Features




Finishes




To complete the product reference, add finish

LED



LED and control gear included




7W  
50°  
drill-hole Ø70  
control gear EL  
650 lm - 3000K **11.0147.1311.33**  
700 lm - 4000K **11.0147.1411.33**




7W  
50°  
drill-hole Ø70  
control gear ELD  
650 lm - 3000K **11.0147.1312.33**  
700 lm - 4000K **11.0147.1412.33**

7W  
50°  
drill-hole Ø70  
control gear ELDD  
650 lm - 3000K **11.0147.1313.33**  
700 lm - 4000K **11.0147.1413.33**

LED



LED and control gear included



7W  
20°  
drill-hole Ø76  
control gear EL  
650 lm  
3000K **0147L/8320**  
4000K **0147L/8420**



7W  
20°  
drill-hole Ø76  
control gear ELD  
650 lm  
3000K **0147L/8320D**  
4000K **0147L/8420D**



7W  
20°  
drill-hole Ø76  
control gear ELDD  
650 lm  
3000K **0147L/8320DD**  
4000K **0147L/8420DD**

7W  
40°  
drill-hole Ø76  
control gear EL  
650 lm  
3000K **0147L/8340**  
4000K **0147L/8440**

7W  
40°  
drill-hole Ø76  
control gear ELD  
650 lm  
3000K **0147L/8340D**  
4000K **0147L/8440D**


7W  
40°  
drill-hole Ø76  
control gear ELDD  
650 lm  
3000K **0147L/8340DD**  
4000K **0147L/8440DD**

Features




Versions:



Special LED versions on request  
DIMMER versions on request (ELD)  
DIMMER DALI versions on request (ELDD)  
2700K and 5000K versions on request





LED and control gear included




<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
13W	13W	13W
15°	24°	36°
drill-hole Ø100	drill-hole Ø100	drill-hole Ø100
control-gear EL	control-gear EL	control-gear EL
1600 lm	1600 lm	1600 lm
3000K <b>11.1604.2831.33</b>	3000K <b>11.1604.2833.33</b>	3000K <b>11.1604.2835.33</b>
4000K <b>11.1604.2841.33</b>	4000K <b>11.1604.2843.33</b>	4000K <b>11.1604.2845.33</b>



<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
18W	18W	18W
15°	24°	36°
drill-hole Ø100	drill-hole Ø100	drill-hole Ø100
control-gear EL	control-gear EL	control-gear EL
2300 lm	2300 lm	2300 lm
3000K <b>11.1604.3831.33</b>	3000K <b>11.1604.3833.33</b>	3000K <b>11.1604.3835.33</b>
4000K <b>11.1604.3841.33</b>	4000K <b>11.1604.3843.33</b>	4000K <b>11.1604.3845.33</b>



<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
25W	25W	25W
15°	24°	36°
drill-hole Ø125	drill-hole Ø125	drill-hole Ø125
control-gear EL	control-gear EL	control-gear EL
3100 lm	3100 lm	3100 lm
3000K <b>11.1604.4831.33</b>	3000K <b>11.1604.4833.33</b>	3000K <b>11.1604.4835.33</b>
4000K <b>11.1604.4841.33</b>	4000K <b>11.1604.4843.33</b>	4000K <b>11.1604.4845.33</b>



<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
32W	32W	32W
15°	24°	36°
drill-hole Ø125	drill-hole Ø125	drill-hole Ø125
control-gear EL	control-gear EL	control-gear EL
4200 lm	4200 lm	4200 lm
3000K <b>11.1604.5831.33</b>	3000K <b>11.1604.5833.33</b>	3000K <b>11.1604.5835.33</b>
4000K <b>11.1604.5841.33</b>	4000K <b>11.1604.5843.33</b>	4000K <b>11.1604.5845.33</b>

Reference options

11.1604.2813.33



11.1604.     .33

- 2- 13W
- 3- 18W
- 4- 25W
- 5- 32W
- 8- On/Off
- 2- Dim 1-10V
- 3- Dali
- 0- Fashion
- 1- Vegetables
- 2- 2700K
- 3- 3000K
- 4- 4000K
- 5- 5000K
- 6- Meat
- 7- Sausages
- 8- Fish
- 9- Bakery
- 1- 15°
- 3- 24°
- 5- 36°



Disperfum, Spain