

e-Wall is a range of recessed LED for walls to provide grazing lighting and beaoning both for outdoors and indoors. Available in different shapes, finishes and sizes.

Features

Outdoor recessed luminaire with stainless steel front and aluminium body. Opal polycarbonate diffuser. Available in versions with slats or diffuser. LEDs and equipment incorporated. It is supplied with a 0.5mts connection cable.



Power

LED 1W, 6,5W

Beam

80°, 120°

Colour temperature

3000K warm white - CRI \geq 80

4000K neutral white - CRI \geq 80

Nominal lumen output

1W - 31 lm / 34 lm, 6,5W - 66 lm / 80lm, 113 lm / 137 lm

Control gear

Electronic (EL)

IP - IK

IP65, IK09, IK10

Finishes

Inox [20]

Supply voltage

220... 240V, 50/60Hz

Installation

Recessed

Features




Polycarbonate protective glass

LED



Diffuser




6,5W
120°
drill-hole 240 x 70
113 lm - 3000K **11.5000.0031.20**
137 lm - 4000K **11.5000.0041.20**

LED and control gear included

LED



Louvers




6,5W
120°
drill-hole 240 x 70
66 lm - 3000K **11.5000.0032.20**
80 lm - 4000K **11.5000.0042.20**

LED and control gear included

LED



Circle




1W
80°
drill-hole Ø71
31 lm - 3000K **11.5000.0033.20**
34 lm - 4000K **11.5000.0043.20**

LED and control gear included

LED



Squared



1W
80°
drill-hole Ø71
31 lm - 3000K **11.5000.0034.20**
34 lm - 4000K **11.5000.0044.20**

LED and control gear included