

The concept of Essence is based on a minimalist and versatile design for complete integration into the surroundings. Luminaires designed around T5 lamps and LED, making the most of its small size to achieve a compact and reduced look.


Features:

Extruded aluminum profile. High purity, specular aluminum reflector recovers the flux of light for greater performance.

Translucent methacrylate diffuser (PMMA) or high-purity aluminium reflector with polycarbonate diffuser.



A simple system has been designed to make different mounting positions possible, and thus, changing the finishing look of the luminaire.



Power

LED 28W, 37W, 48W
T5-HE 28W
T5-HO 54W

Beam

86°

Colour temperature

3000K warm white - CRI ≥ 80
4000K neutral white - CRI ≥ 80

Nominal lumen output

28W - 3510lm, 37W - 4680lm, 48W - 5980lm

Control gear

Electronic (EL) - (CP)
Electronic Dimmer (ELD) - (CPD)
Electronic Dimmer Dali (ELDD) - (CPDD)

IP

IP40

Finishes

White (33)
Grey (21)

Supply voltage

220... 240V, 50/60Hz

Installation

Recessed ceiling




Features



Translucent polycarbonate diffuser (PMMA)

Finishes





To complete the product reference, add finish

Versions: 2700K Available / Under demand

SINGLE module LED



LED and control gear included



28W L= 942,5
37W L= 1242,5
48W L= 1542,5



28W
86°
drill 55x920
control-gear EL
3510 lm
3000K **138E/L0983**
4000K **138E/L0984**



28W
86°
drill 55x920
control-gear ELDD
3510 lm
3000K **DD138E/L0983**
4000K **DD138E/L0984**



37W
86°
drill 55x1220
control-gear EL
4680 lm
3000K **138E/L1283**
4000K **138E/L1284**



37W
86°
drill 55x1220
control-gear ELDD
4680 lm
3000K **DD138E/L1283**
4000K **DD138E/L1284**



48W
86°
drill 56x1520
control-gear EL
5980 lm
3000K **138E/L1583**
4000K **138E/L1584**




48W
86°
drill 56x1520
control-gear ELDD
5980 lm
3000K **DD138E/L1583**
4000K **DD138E/L1584**

Module continuous lines LED



LED and control gear included



28W L= 908,5
37W L= 1208,5
48W L= 1508,5

WITHOUT COVERS
+13,5 x COVER (accessories)



28W
86°
drill 45x916 with covers
control-gear EL
3510 lm
3000K **138E/LA0983**
4000K **138E/LA0984**



28W
86°
drill 920 with covers
control-gear ELDD
3510 lm
3000K **DD138E/LA0983**
4000K **DD138E/LA0984**



37W
86°
drill 45x1220 with covers
control-gear EL
4680 lm
3000K **138E/LA1283**
4000K **138E/LA1284**



37W
86°
drill 45x1220 with covers
control-gear ELDD
4680 lm
3000K **DD138E/LA1283**
4000K **DD138E/LA1284**



48W
86°
drill 45x1520 with covers
control-gear EL
5980 lm
3000K **138E/LA1583**
4000K **138E/LA1584**



48W
86°
drill 45x1520 with covers
control-gear ELDD
5980 lm
3000K **DD138E/LA1583**
4000K **DD138E/LA1584**

Accessories

End-cap for start and end of the straight line (1 unit)
40/138E

Aligner for continuous lines
ALC/138E

Features




Finishes



SINGLE module T5

G5 T5-HE



28W
86°
drill 56x1190
control gear CP
3000K **138E/12883**
4000K **138E/12884**



28W
86°
drill 56x1190
control gear CPD
3000K **D138E/12883**
4000K **D138E/12884**



28W
86°
drill 56x1190
control gear CPDD
3000K **DD138E/12883**
4000K **DD138E/12884**

Lamp and control gear included



G5 T5-H0



54W
86°
drill 56x1190
control gear CP
3000K **138E/15483**
4000K **138E/15484**




54W
86°
drill 56x1190
control gear CPD
3000K **D138E/15483**
4000K **D138E/15484**



54W
86°
drill 56x1190
control gear CPDD
3000K **DD138E/15483**
4000K **DD138E/15484**

Lamp and control gear included





Centro Cívico Palencia, Spain