

The concept of Essence is based on a minimalist and versatile design for complete integration into the surroundings. Luminaires designed around LED making the most of its small size to achieve a compact and reduced look.

Features:

Extruded aluminum profile. High purity, specular aluminum reflector recovers the flux of light for greater performance.

Translucent methacrylate diffuser (PMMA) or high-purity aluminium reflector with polycarbonate diffuser.

Fitting:

Several installation options: hanging, ceiling or wall-mounted.

Hanging models are suspended from a steel cable. Suspension elements not included. Accessories needed.

Fitted as an independent module and forming continuous lines.



Power

LED 14W, 19W, 24W, 28W, 37W, 48W

T5-HE 28W

T5-HO 54W

Beam

LED 86°

Colour temperature

3000K warm white - CRI \geq 85

4000K neutral white - CRI \geq 85

Nominal lumen output

14W - 1500lm, 15W - 2258lm, 19W - 2300lm, 19,5W - 2700lm, 20W - 3100lm, 24W - 3150lm, 27W - 3600lm, 29W - 360 lm, 34W - 4050 lm, 40W - 4670 lm

Control gear

Electronic (EL) - (CP)

Electronic Dimmer Dali (ELDD) - (CPDD)

IP

IP40

Finishes

Black (04)

White (33 - 63)

Grey (21)

Supply voltage

220... 240V, 50/60Hz

Accessories


Suspension systems

Features



Translucent polycarbonate diffuser (PMMA)
For hanging versions, accessories are required
End caps included.

Finishes



To complete the product
reference, add finish

Versions: 2700K Available / on request


SINGLE module LED

LED

Hanging or ceiling mounted

LED and control gear included

Can be fitted in continuous lines
(see accessories)



14W 86° 1500 lm control gear EL 3000K 137/L0983 4000K 137/L0984	19W 86° 2300 lm control gear EL 3000K 137/L1283 4000K 137/L1284	24W 86° 2900 lm control gear EL 3000K 137/L1583 4000K 137/L1584


28W 86° 3510 lm control gear EL 3000K 138/L0983 4000K 138/L0984	37W 86° 4680 lm control gear EL 3000K 138/L1283 4000K 138/L1284	48W 86° 5980 lm control gear EL 3000K 138/L1583 4000K 138/L1584

14W 86° 1500 lm control gear ELDD 3000K DD137/L0983 4000K DD137/L0984	19W 86° 2300 lm control gear ELDD 3000K DD137/L1283 4000K DD137/L1284	24W 86° 2900 lm control gear ELDD 3000K DD137/L1583 4000K DD137/L1584

28W 86° 3510 lm control gear ELDD 3000K DD138/L0983 4000K DD138/L0984	37W 86° 4680 lm control gear ELDD 3000K DD138/L1283 4000K DD138/L1284	48W 86° 5980 lm control gear ELDD 3000K DD138/L1583 4000K DD138/L1584

Wall-mounted


LED and control gear included



28W 86° 3510 lm control gear EL 3000K 138AP/L0983 4000K 138AP/L0984	37W 86° 4680 lm control gear EL 3000K 138AP/L1283 4000K 138AP/L1284	48W 86° 5980 lm control gear EL 3000K 138AP/L1583 4000K 138AP/L1584

Track

LED and control gear included



28W 86° 3510 lm control gear EL 3000K 138L/0983T 4000K 138L/0984T	37W 86° 4680 lm control gear EL 3000K 138L/1283T 4000K 138L/1284T	48W 86° 5980 lm control gear EL 3000K 138L/1583T 4000K 138L/1584T

Features



Translucent polycarbonate diffuser (PMMA)
For hanging versions, accessories are required
End caps included.

Finishes




To complete the product
reference, add finish

G5 **T5-HE**

Hanging or ceiling mounted

Control gear included





28W
control gear CP
3000K **138/12883**
4000K **138/12884**

28W
control gear CPD
3000K **D138/12883**
4000K **D138/12884**

28W
control gear CPDD
3000K **DD138/12883**
4000K **DD138/12884**

Wall-mounted

Control gear included



28W
control gear CP
3000K **136AP/12883**
4000K **136AP/12884**



28W
control gear CPD
3000K **D136AP/12883**
4000K **D136AP/12884**

28W
control gear CPDD
3000K **DD136AP/12883**
4000K **DD136AP/12884**

G5 **T5-HO**

Hanging or ceiling mounted

Control gear included




54W
control gear CP
3000K **138/15483**
4000K **138/15484**

54W
control gear CPD
3000K **D138/15483**
4000K **D138/15484**

54W
control gear CPDD
3000K **DD138/15483**
4000K **DD138/15484**

Wall-mounted

Control gear included



54W
control gear CP
3000K **136AP/15483**
4000K **136AP/15484**

54W
control gear CPD
3000K **D136AP/15483**
4000K **D136AP/15484**

54W
control gear CPDD
3000K **DD136AP/15483**
4000K **DD136AP/15484**

Finishes



To complete the product reference, add finish

Suspension systems



Suspension without connection.
138/511



Suspension with connection - 3 poles
138/510



Intermediate hanging
138M/511



Suspension with connection - 5 poles
138D/510

Aligner for continuous lines
for ref. 136AP...,137...,138...
ALC/138

