

External LED spotlights suitable for hard to reach areas, facades, fences, roofs...

The construction materials are resistant to weathering and vandalism.

Features

Body built in aluminium. Protective glass.

Suitable to be surface mounted in walls, ceilings.



WHITOUT sensor



WHIT sensor



Power

LED 9,2W, 25W, 50W, 90W, 180W

Beam

100°, 110°

Colour temperature

4000K warm white - CRI \geq 80

Nominal lumen output

9,2W - 1269 lm, 25W - 3292 lm, 45W - 6344lm, 90W - 12186 lm, 180W - 25092 lm

Control gear

Electronic (EL)

IP - IK

IP65 - IK08

Finishes

Black (04 - 204)


Supply voltage

100...240V, 50/60 HZ


Installation

Walls, ceilings

Features




LED



9,2W
100°
1269 lm
4000K **11.5100.1401.04**

9,2W
100°
1269 lm
SENSOR
4000K **11.5100.1409.04**

LED and control gear included






25W
100°
3292 lm
4000K **11.5100.3401.04**

25W
100°
3292 lm
SENSOR
4000K **11.5100.3409.04**



LED and control gear included

LED





45W
110°
6344 lm
4000K **5100/L284/204**

LED and control gear included



90W
110°
12186 lm
4000K **5100/L384/204**

LED and control gear included



180W
110°
25092 lm
4000K **5100/L484/204**

LED and control gear included