

Mini-up is a full program of small recessed lights with LED in various colours, that provides low level perimeter illumination for safe orientation as step or exit signing, etc. Available in round and square shapes, Mini-Up is most suitable on walkways areas and has a variety of uses.

Features

Recessed luminaire with injected aluminium body, painted with protection for the outdoors. Stainless steel front in two versions, round and square. Tempered 5mm thick glass. It holds a weight of 780Kg. It is supplied with PVC niche. 20-degree opening angle. It is supplied with a 0.5mts connection cable.

IP68 version available, suitable for submersible installations.

Built-in system, except for submersible versions.



Iberostar hotel, Mexico

Power

LED 3W

Beam

20°

Colour temperature

3000K - cold white - CRI ≥ 80

4000K - neutral white - CRI ≥ 80

Nominal lumen output

2,6W - 139 / 174 lm, 3W - 120 / 139 lm

Control gear

Electrónico (EL)

IP - IK

IP67, IP68, IK06, IK09

Finishes

Inox [20]

Supply voltage

220... 240V, 50/60Hz

24VDC (versión sumergible)

Installation

Recessed

Features



Housing included

<p>LED</p> <p>IP 67 IK 08</p> <p>Resistance 780Kg</p> <p>LED and control gear included</p>			<p>3W 20° drill Ø 90 120 lm - 3000K 11.5200.0031.20 139 lm - 4000K 11.5200.0041.20</p>
<p>LED</p> <p>IP 67 IK 08</p> <p>Resistance 780Kg</p> <p>LED and control gear included</p>			<p>3W 20° drill Ø 90 120 lm - 3000K 11.5200.0032.20 139 lm - 4000K 11.5200.0042.20</p>
<p>LED</p> <p>IP 68 IK 06</p> <p>LED and control gear included</p>			<p>2,6W 20° drill Ø 136 139 lm - 3000K 11.5200.0033.20 174 lm - 4000K 11.5200.0043.20</p>

