

Nix is a range of hermetic screens for T5 lamps with a huge variety of installation types, wall or ceiling mounted, or hanging. Luminaires especially suitable for lighting premises requiring a high level of protection from the surroundings: high degree of humidity, air pollution, risk of impacts...

Features:

Housing in injected polycarbonate, reflecting plate in enamelled steel, and methacrylate diffuser stabilized against UV rays and fixed to the luminaire by clips which are fully integrated into the housing.


Power

LED 12W, 25W, 30W, 50W, 60W

Ópticas

120°

Colour temperature

4000K neutral white - CRI ≥ 80

Nominal lumen output

12W - 1120lm, 25W - 2252lm, 30W - 2875lm, 50W - 4956lm, 60W - 6023lm

Control gear

Electronic (EL)

Electronic Dimmer (ELD)

Electronic Dimmer Dali (ELDD)

IP

IP65 - IK10

Finishes

Grey [21]

Supply voltage

220...240V, 50/60Hz


Installation

Adosada

Features




LED and control gear included



12W L= 600

12W
120°
control gear EL
1120 lm
4000K **11.0030.1411.21**




25W L= 600

25W
120°
control gear EL
2304 lm
4000K **11.0030.1401.21**


25W
120°
control gear ELD
2304 lm
4000K **11.0030.1402.21**

25W
120°
control gear ELDD
2304 lm
4000K **11.0030.1403.21**



25W L= 1200

25W
120°
control gear EL
2252 lm
4000K **11.0030.2411.21**




50W L= 1200

50W
120°
control gear EL
4956 lm
4000K **11.0030.2401.21**


50W
120°
control gear ELD
4956 lm
4000K **11.0030.2402.21**

50W
120°
control gear ELDD
4956 lm
4000K **11.0030.2403.21**



30W L= 1500

30W
120°
control gear EL
2875 lm
4000K **11.0030.3411.21**



60W L= 1500

60W
120°
control gear EL
6023 lm
4000K **11.0030.3401.21**

60W
120°
control gear ELD
6023 lm
4000K **11.0030.3402.21**

60W
120°
control gear ELDD
6023 lm
4000K **11.0030.3403.21**