


•

Luminaires designed to create spaces with character by using high quality and architectural lighting. "Patos Line" is perfect to give an actual and modern touch to museums, galleries, offices, clubs, restaurants and hotels.



Patos



Patos line



informacja

<< Poradnia Genetyczna
<< Pracownia Mammografii

Body built in aluminium with an excellent light transmittance-index prismatic diffuser. Electronic gear built in the luminaire.

**Power**

LED from 10W to 90W

Beam

115°

Colour temperature

3000K warm white - CRI $\geq$ 80

4000K neutral white - CRI $\geq$ 80

Nominal lumen output

10W - 1400lm, 30W - 4200lm, 60W - 8400lm, 70W - 9800lm,

90W - 12600lm

Control gear

Electronic (EL)

IP

IP20

Finishes

White

Supply voltage

220...230V, 50/60Hz

Installation



Recessed ceiling

Features



LED

LED and control gear included



10W
1400 lm
drill Ø330
3000K **AG0A1POCLEDAPLX31**
4000K **AG0A1POCLEDAPLX21**



30W
4200 lm
drill Ø476
3000K **AG0A1PODLEDAPLX31**
4000K **AG0A1PODLEDAPLX21**



60W
8400 lm
drill Ø676
3000K **AG0A1POFLEDAPLX31**
4000K **AG0A1POFLEDAPLX21**



70W
9800 lm
drill Ø826
3000K **AG0A1POGLEDAPLX31**
4000K **AG0A1POGLEDAPLX21**



90W
12600 lm
drill Ø1026
3000K **AG0A1POHLEDA1PLX31**
4000K **AG0A1POHLEDA1PLX21**



Body built in aluminium with PMMA prismatic diffuser. Electronic gear built in the luminaire. Ceiling and wall recessed installation being possible to create continuous lines.

**Power**

LED 21W, 34W

Beam

90°

Colour temperature4000K neutral white - CRI $\geq$ 80**Nominal lumen output**

21W - 2600lm, 34W - 4400lm

Control gear

Electronic (EL)

IP

IP20

Finishes

White

Supply voltage

220...230V, 50/60Hz

Installation

Recessed ceiling

Accessories


Connector

Features



LED


LED and control gear included



SINGLE module version


☐	☐
21W	34W
2600 lm	4400 lm
Drill 80 x 1141	Drill 80 x 1141
4000K AG0A1PPLL22APLX	4000K AG0A1PPLL40APLX

LEFT module




☐	☐
21W	34W
2600 lm	4400 lm
4000K AG0A1PLLA26APLX	4000K AG0A1PLLA44APLX

RIGHT module



☐	☐
21W	34W
2600 lm	4400 lm
4000K AG0A1PLLB26APLX	4000K AG0A1PLLB44APLX

MIDDLE module



☐	☐
21W	34W
2600 lm	4400 lm
4000K AG0A1PLLC26APLX	4000K AG0A1PLLC44APLX

Accessories

Connector

AG0A1PLL-LED	Connector lineal
AG0E1PL-L	Connector L
AG0E1PL-T	Connector T
AG0E1PL-+	Connector +
AG0A1PLL-LED-SS	Connector wall-ceiling