

Small-Up is a set of recessed LED with an outer ring of stainless steel designed for floorings. Can be installed both outdoors and indoors. Its function is to illuminate and signal passageways.

Features

Body made of die-cast aluminium with stainless steel front. 8mm tempered glass protection screen. The adjustable version holds loads up to 780Kg and up to 2.500Kg in case of the fixed version. Versions for grazing lighting in one, two or four openings, with capacity to hold up to 2.000Kg.

It is supplied with a 0.5mts connection cable. It is supplied with PVC niche. LED and equipment incorporated.

The adjustable version has an outdoor gobo for adjustment.



Iberostar Hotel, Mexico

Power

LED 6W

Beam

20° - 1 Beam - 2 Beams - 4 Beams

Colour temperature

3000K cold white - CRI \geq 80

4000K warm white - CRI \geq 80

Nominal lumen output

6W - 376 / 478 lm

Control gear

Electronic (EL)

IP - IK

IP67, IK09, IK10

Finishes

Inox [20]

Supply voltage

220... 240V, 50/60Hz

Installation


Recessed floor

Features




Housing included

LED

IK 09 

Fixed
Resistance 2.500Kg

LED and control gear included




6W
20°
376 lm - 3000K **11.5202.0031.20**
478 lm - 4000K **11.5202.0041.20**

LED

IK 09 


Orientable 30°
Resistance 780Kg

LED and control gear included




6W
20°
376 lm - 3000K **11.5202.0032.20**
478 lm - 4000K **11.5202.0042.20**

LED

IK 10 


Resistance 2.000Kg

LED and control gear included




6W
1 beam
376 lm - 3000K **11.5180.0031.22**
478 lm - 4000K **11.5180.0041.22**

LED

IK 10 


Resistance 2.000Kg

LED and control gear included




6W
2 beams
376 lm - 3000K **11.5180.0032.22**
478 lm - 4000K **11.5180.0042.22**

LED

IK 10 

Resistance 2.000Kg

LED and control gear included



6W
4 beams
376 lm - 3000K **11.5180.0033.22**
478 lm - 4000K **11.5180.0043.22**

