

Family of cylindrical projectors and big formal simplicity that thank to a timeless design allows a high degree of integration in many architectural spaces without interfere in their aesthetics.

Under a universal appearance, Spoty, integrates the most sophisticated LED light sources and different perspective accent that makes a more suitable application in commercial spaces, window displays or large indoor spaces.

Features

Constructed of aluminum. It incorporates a system of orientation by fork allowing a vertical turn of 90° and a 360° horizontal rotation.

The applied LED technology gives them a long service life, a luminous flow maintenance and a color rendering index over the life of the product.

Available in both semi-intensive and extensive that integrate faceted reflectors in high purity aluminum. LED auxiliary equipment are integrated into the body of the luminaire.



LED personalisation

Option to incorporate new light sources designed to offer excellent colour reproduction to create products for very specific segments. On request.



Power

LED 25W, 38W

Beam

20°, 40°, Wall washer 15°

Color temperature

3000K warm white - CRI ≥ 80
4000K neutral white - CRI ≥ 80

Nominal lumen output

25W - 3500 lm, 37W - 5100 lm

Control gear

Electronic (EL)
Electronic Dimmer (ELD)
Electronic Dimmer Dali (ELDD)

IP

IP20

Finishes

White (33)
Grey (21)
Black (04)

Supply voltage

220... 240V, 50/60Hz

Installation

Three-phase electric track and base


Accessories

Base

Features




Finishes




To complete the product reference, add finish

Versions:

Special LED versions on request
 DIMMER versions on request
 2700K and 5000K versions on request



LED and control gear included



■ □ □
 25W
 20°
 track³ / track^{3e}
 3500 lm
 3000K **798L/M8320**
 4000K **798L/M8420**

■ □ □
 25W
 40°
 track³ / track^{3e}
 3500 lm
 3000K **798L/M8340**
 4000K **798L/M8440**


37W
 20°
 track³ / track^{3e}
 5100 lm
 3000K **799L/M8320**
 4000K **799L/M8420**

37W
 40°
 track³ / track^{3e}
 5100 lm
 3000K **799L/M8340**
 4000K **799L/M8440**



Wall washer

LED and control gear included



■ □ □
 25W
 wall washer 15°
 track³ / track^{3e}
 3500 lm
 3000K **798L/M8315**
 4000K **798L/M8415**

37W
 wall washer 15°
 track³ / track^{3e}
 5100 lm
 3000K **799L/M8315**
 4000K **799L/M8415**



■ □ □
 Surface base for spotlights with
 tree-phase adapter
2427

Reference options

799L/M8220/33



79 □ L/M □ □ □ □ / □ □ □ □

8- 25W
 9- 37W

00- Fashion
 01- Vegetables
 02- 2700K
 03- 3000K
 04- 4000K
 05- 5000K
 06- Meat
 07- Sausages
 08- Fish
 09- Bakery

15- Wall washer 15°
 20- 20°
 40- 40°

04- Black
 21- Grey
 33- White

Reference options for control gear

79 □ L/M □ □ □ □ D / □ □

D= Dim 1-10V

79 □ L/M □ □ □ □ DD / □ □

DD= DALI